



NORDIC PINE (ECOTHERMO)

THICKNESS X WIDTH
FACE COVER: 20x65 mm
WOOD SPECIE: Nordic Pine
(EcoThermo)
BOARD: Brushed solid wood

PROFILE: Trapézo
SHADE: Irisé 108
Ref. 461

sivalbp
bois, technologie & design



Medical Social Centre of Auray - Architect: DLW Architectes - Photographer François Dantart

PROFILE: TRAPÉZO 20x65



END-MATCHED

- **Rounded edges** for a better lasting of the finish.
- **End-matched:** simplifies installation and reduces the cutting wastage.

CHARACTERISTICS

- EcoThermo solid wood board.
- **Trapézo profile, end-matched:** facilitates the fitting and reduces the cutting wastage.
- **Brushed surface:** it gives an optimal and texture surface; it brings out the natural grain and increases penetration and efficiency of the coating.
- **Class 3.1 preservation, CTBB+ certified, sprayed on the 4 sides.**
- New generation **preservation: fungicide, anti-bluestain, insecticide, anti-termite.**
- Finish:
 - > **Water-based penetrating finish made with acrylic resin and natural mineral pigment** (chemical free).
 - > Industrial quality finish applied under strictly controlled factory conditions, ensuring consistent and uniform application.
 - > Application of a finish on the reverse side ensuring a good balance of the board.
- The durability of the wood is guaranteed for 10 years with preservation.
- The Sivalbp **New Age** finish allows to delay the natural ageing process for minimum 3 years, according to exposure and building's architecture. Nordic Pine, lasting up to 50 years.



SIVALBP

- EcoThermo external cladding, environmentally friendly.
- Excellent dimensional stability and durability
 - Neutralizes resin pockets
 - Suitable for all climatic conditions
- A non film forming finish that penetrates into the wood and does not flake over time.
- Without maintenance, this finish will turn into a natural grey and a contemporary uniform appearance over time.

SHADE: IRISÉ 108



WOOD SPECIE: NORDIC PINE (ECOTHERMO)

Nordic Pine: Scandinavian timber, lasting-up to 50 years, **PEFC certified (PEFC/10-31-1593).**

Singularities and knots: slow-growing essence; fine veining; medium knots.

Available only with our EcoThermo process.



Promoting
Sustainable Forest
Management
www.pefc-france.org



- Friendly environmental process and chemical free
- Exceptional durability and stability
- Better resistance to the weather



NF EN 14915
All our boards
are compliant
with CE marking

| WOOD SPECIE | THERMAL PROCESS | DURABILITY | TECHNICAL PROPERTIES | | |
|---|---|---|--|--|--|
| Nordic Pine Geographical area: Scandinavia Quality: A/B choice NF EN 14519 | Thermostabilisation Ecological process, environmentally friendly and chemical free. It consists in moisturising and heating the wood to high temperature. This process gives the boards exceptional durability and stability and greatly reduces the shrinkage phenomenon. The wood acquires an even, brown colour all the way through and neutralizes resin exudation. | Use class: 3.1 with the Sivalbp preservation certified CTB B+ | Behavioural fire restrictions | Thermal characteristics according to NF EN 12 524 | Water vapour permeability according to NF EN 12 524 |
| PEFC certified | | | EUROCLASSE D-s2, d0 for reaction to fire (according to 14915 NF EN standard) | Thermal resistance R in m ² . K/W: 0,13 | Water vapour resistance: 72 µ |
| Carbon footprint: 4.82 kg CO ₂ eq./m ² (module D excluded)* | | Nordic Pine, lasting up to 50 years | Combustible mass in MJ/m ² : 136 | | Average density : 520 kg/m ³ to 12% wood moisture content |

* Consult our Environmental and Health Declaration Sheets on the INIES database

| MECHANICAL PROPERTIES | | | | | |
|---|---|-------------------------------|---|---|--|
| Breaking stress in compression: NC* N/mm ² | Breaking stress in tension: NC* N/mm ² | Breaking stress in shear: NC* | Breaking stress in bending: NC* N/mm ² | Modulus of elasticity in bending: NC* N/mm ² | Compliant for French implementation in Q4 area (impact resistance) |

| PREPARATION FINISH | SHADE | THICKNESS X WIDTH FACE COVER IN MM | BOARD | LENGTHS (M)* (saccording to availability) | FITTING | PACKAGING |
|--|-----------|------------------------------------|--------------------|---|--|---------------------------|
| Brushed solid wood 1 coat of saturator by spraying on the facing 1 coat of white stain for counter-balancing | Irisé 108 | 20x65 mm | Brushed solid wood | 3.60 - 3.90 - 4.20 - 4.50 - 4.80 - 5,10 m | 1 nail in the center of the slot for a 40 cm distance between centres + double up the nails at the ends (find installation advice below) | Packs x boards/pack: 96x6 |

*For solid wood boards with end-matched, the effective length is equal to the standard supply length invoiced minus 30 millimeters.
 NPD: not performance declared. NC: non communicated.

INSTALLATION ADVICES





To ensure the products are correctly installed, the rules laid out in the French code of practice DTU 41.2 for external cladding, and our Technical Guide, should be observed.

- Store the boards in a dry place, sheltered from the elements and ventilated.
- **Can be fitted vertically only:** mandatory double battening.
- Cladding must be fixed on batten with a minimum of 27 mm thickness (32 mm for UK).
- The distance of the secondary framework must be attached at a minimum of 40 cm and a maximum of 65 cm apart. Single fixing on visible cladding for 40 cm distance between centers. Double fixing on visible cladding for a distance between centres between 40 cm and 65 cm maximum.
- A waterproof membrane satisfying the standard must be installed (except for walls which are already watertight, solid concrete walls).
- **Mandatory air gap** behind Sivalbp cladding to ensure a good ventilation. The air outlets must be at the base and the top of the cladding elevation.
- Ensure a minimum of 20 cm above ground clearance.
- Assembly by interlocking (end-matched on the 4 sides).
- Fastening with **stainless steel screws or stainless steel tips**, twisted or ringed.
- The head of the nails or screws must not penetrate further than 1 mm into the boards.
- **All the cuts must be touched up with Sivalbp-New Age paint.** We also recommend that the ends of the boards should also be treated.

ACCESSORIES AND FINISH CUTS TOUCH UP

- Accessories available in 1 shade: irisé 108
- Available finish cuts touch up in tins of 1L or 5L: all cuts must be touched up (see French DTU 59.1)

| Profile |  |  |
|------------------------------------|---|---|
| Product | Complex corner trim | Board |
| Surface finish | Sanded finger-jointed | Sanded glulam |
| Thickness x width face cover in mm | 67x55 | 25x270 |

MAINTENANCE

- To maintain the bright of colors, clean annually by lightly brushing the surface (avoid high pressure cleaners).
- This gray finish will evolve naturally and very gradually over time.
- If necessary and according to the exposure and the architecture of the building, renovation of the color is facilitated without stripping or sanding.
- As soon as necessary, apply Sivalbp **New Age** saturator directly a spray or paintbrush in 1 or 2 coats to re-saturate the wood fibers.
- A sustained finish will help to preserve the cladding.
- We advise you to contact a professional who will apply the appropriate renovation procedure.

GENERAL REMARK

Wood is a natural and heterogeneous material. It may have singularities such as knots, cracks, splits, resin pockets. Etc



Find all of our **DOCUMENTATION** on our website: sivalbp.fr



Get our installation advice in the SIVALBP **TECHNICAL GUIDE**



Download our **MAINTENANCE BOOKLET** for our maintenance recommendations

sivalbp[®]
bois, technologie & design